



SOLAR N PLUS

SP-N16/108HG

N-TYPE Bifacial 420-450W



HIGHER
EFFICIENCY



LOWER TEMPERATURE
COEFFICIENT



LOW ATTENUATION,
LONG WARRANTY



HIGHER
BIFACIALITY


WARRANTY



Guarantee on product material
and workmanship



Linear power
output warranty



INSURANCE



中国平安
PINGAN

CERTIFICATION



- ISO 9001: 2015/quality management system
- ISO 14001: 2015/environment management system
- ISO 45001: 2018/occupation health safety management system

420-450W

SP-N16/108HG

ELECTRICAL CHARACTERISTICS (STC)

Maximum Power (Pm)	W	420	425	430	435	440	445	450
Power Tolerance	W	0~+5						
Maximum Power Voltage (Vm)	V	33.3	33.5	33.7	33.9	34.1	34.3	34.5
Maximum Power Current (Im)	A	12.61	12.69	12.76	12.83	12.91	12.98	13.05
Open Circuit Voltage (Voc)	V	38.85	39.05	39.25	39.45	39.65	39.85	40.05
Short Circuit Current (Isc)	A	13.46	13.51	13.56	13.61	13.66	13.71	13.76
Module Efficiency (ηm)	%	21.5	21.8	22.0	22.3	22.5	22.8	23.0

STC: AM=1.5, irradiance=1000W/m², module temperature=25°C

ELECTRICAL CHARACTERISTICS (NMOT)

Maximum Power (Pm)	W	316	320	324	328	332	336	340
Maximum Power Voltage (Vm)	V	30.44	30.68	30.92	31.15	31.35	31.55	31.72
Maximum Power Current (Im)	A	10.38	10.43	10.48	10.53	10.59	10.65	10.72
Open Circuit Voltage (Voc)	V	36.70	36.90	37.10	37.30	37.50	37.70	37.89
Short Circuit Current (Isc)	A	10.81	10.86	10.91	10.96	11.00	11.05	11.10

NMOT: irradiance=800W/m², environment temperature=20°C, wind speed=1m/s

REAR SIDE POWER GAIN

5%	Max Power	441	446	452	457	462	467	473
	Efficiency	22.58%	22.85%	23.12%	23.39%	23.66%	23.93%	24.20%
15%	Max Power	483	489	495	500	506	512	518
	Efficiency	24.73%	25.03%	25.32%	25.62%	25.91%	26.21%	26.50%
25%	Max Power	525	531	538	544	550	556	563
	Efficiency	26.89%	27.21%	27.53%	27.85%	28.17%	28.49%	28.81%

MECHANICAL SPECIFICATIONS

External Dimension (L×W×H)	1722×1134×30mm
Weight	24kg
Number of Cells	108 (6×18)
Front Glass	2.0mm AR-coating heat-strengthened glass
Rear Glass	2.0mm heat-strengthened glass
Frame	Anodized aluminum alloy, Black color
Junction Box	IP68
Output Cables	4mm², 300mm or customized length
Connector	MC4 Compatible



APPLICATION CONDITIONS

Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	25A
Operating Temperature	-40°C ~ +85°C
Mechanical Load	5400Pa/2400Pa
Hail Test	25mm diameter hail at 23m/s
Bifaciality	80±5%
Application Rating	Class A

TEMP CHARACTERISTICS


Nominal Module Operating Temperature	42±2°C
Temperature Coefficient of Pmax	-0.29%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of ISC	0.045%/°C

TECHNICAL DRAWING




I-V CURVE

I-V characteristics at different irradiance (SP-N16/108HG450W)



I-V characteristics at different temperatures (SP-N16/108HG450W)



PACKING CONFIGURATION

Container	40'HC
Pieces per Pallet	37 pcs
Packaging box Size	1779×1145×1260mm
Pieces per Container	962 pcs



SOLAR N PLUS NEW ENERGY TECHNOLOGY CO., LTD

No.1 Jianye road, Zhongxin Suchu Industrial Development Zone, Chuzhou City, 239000, Anhui Province, China
025-52806120
www.solarnplus.com

Solar N Plus reserves the sole right of interpretation.
Version No.20250625V4.1